

New



Perfect for any maintenance or repair application, the 2115QTiMAX delivers maximum power and control, along with unmatched reliability that comes from more than a century of proven engineering and innovation.

- 407 Nm (300 ft-lb) of maximum torque in reverse - that's the best-in-class performance.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Titanium hammercase is lightweight with unparalleled durability.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.
- FREE two-year limited warranty with tool registration.

Specifications at 6,2 bar (90 psi)

Part Number	2115QTiMAX
Ordering number	45587326
Drive size (square)	3/8 in
Available versions:	
- 1/2" square drive	2125QTiMAX

PERFORMANCE

Working torque in forward	25 - 230 ft-lb / 34 - 312 Nm
Maximum torque in forward	250 ft-lb / 339 Nm
Working torque in reverse	280 ft-lb / 380 Nm
Maximum torque in reverse	300 ft-lb / 407 Nm
Recommended fastener size	7/16 in / M11
Free speed	15 000 rpm
Impacts per minute	1 500

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4,0 CFM / 113 L/min
Air consumption at load	17,0 CFM / 481 L/min

NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	93,2 / 104,2 dB(A)
Free speed sound pressure / power (ISO15744)	89,7 / 100,7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	7,5 / 1,8 m/s ²

WEIGHT & DIMENSIONS

Tool weight	2.49 lb / 1,13 kg
Tool dimensions (L x W x H)	151 x 56 x 171 mm
Shipping weight	3.29 lb / 1,50 kg
Shipping dimensions (L x W x H)	238 x 213 x 79 mm
UPC / EAN code	6 63023 04313 5
Origin	Assembled in the USA



www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



SK3M10
81287344
3/8" Impact socket set (10 pcs) (9, 10, 11, 12, 13, 14, 15, 16, 17 and 19 mm)



Impact sockets
For the complete range, see our accessory catalogue.



2112-366
10323350
Horizontal hanger



BMDS-2
92842152
Cable balancer, 1-2,5 kg, 2 m (6-1/2 ft)



2115-BOOT
45505351
Protective tool boot



2115-K284
45612637
Piped-away exhaust kit



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7,2 mm bore (EURO 7,2 - 7,4)



Quick Release Couplings
For the complete range, see our accessory catalogue.



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



115-LBK1
04616108
Lubricant kit for Impactools™ with composite housing



10Z4
03875671
Oil, Class 1, no. 10, 0,12 L



115-4T-6
04618948
Grease for Impactools with composite housing (6 tubes)



Lubricants
For the complete range, see our accessory catalogue.



2115-THK2
45585932
Impact mechanism service kit



2115-TK2
45585189
Motor service kit