



Perfect for any maintenance or repair application, the 2135QPTiMAX delivers maximum power and control, along with unmatched reliability that comes from more than a century of proven engineering and innovation.

- 1 057 Nm (780 ft-lb) of maximum torque in reverse - that's the best-in-class performance.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Titanium hammercase is lightweight with unparalleled durability.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- Optional piped-away exhaust system can further reduce noise level and directs air away from the operator.
- FREE two-year limited warranty with tool registration.

Specifications at 6.2 bar (90 psi)

Part Number	2135QPTiMAX
Ordering number	45535572
Drive size (square)	1/2 in
Socket retainer type	pin-type

PERFORMANCE

Working torque in forward	50 - 550 ft-lb / 68 - 746 Nm
Maximum torque in forward	600 ft-lb / 813 Nm
Working torque in reverse	650 ft-lb / 880 Nm
Maximum torque in reverse	780 ft-lb / 1 057 Nm
Recommended fastener size	9/16 in / M14
Free speed	9 800 rpm
Impacts per minute	1 250

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Air consumption at load	24.0 CFM / 11.3 L/s

NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	94.2 / 105.2 dB(A)
Free speed sound pressure / power (ISO15744)	86.0 / 97.0 dB(A)
Vibration level / measurement uncertainty (ISO28927)	13.3 / 4.6 m/s ²

WEIGHT & DIMENSIONS

Tool weight	4.05 lb / 1.84 kg
Tool dimensions (L x W x H)	187 x 69 x 183 mm
Shipping weight	4.85 lb / 2.20 kg
Shipping dimensions (L x W x H)	238 x 213 x 79 mm
UPC / EAN code	6 63023 03723 3
Origin	Assembled in the USA





SK4M14
81287351
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)

Impact sockets

For the complete range, see our accessory catalogue.



2131-366
04706388

Horizontal hanger



2135-BOOT
45505377
Protective tool boot



33104
91486330
Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



115-LBK1
04616108
Lubricant kit for Impacttools™ with composite housing



115-4T
04616157
Grease for Impacttools with composite housing



2135PTi-THK1
80122153
Impact mechanism service kit



SK4M18
81287385
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)

4UA9

03070216
1/2" right-angle head
(speed reduction: 25%
torque output reduction: up to 50%)



BMSD-4
92842087

Cable balancer, 2-4 kg, 2 m (6-1/2 ft)



2115-K284
45612637
Piped-away exhaust kit



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



Quick Release Couplings

For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



Lubricants
For the complete range, see our accessory catalogue.



2135-TK2
45535028
Motor service kit