



Perfect for any maintenance or repair application, the 2130XP delivers plenty of power in a lightweight and ergonomic package.

- 816 Nm (602 ft-lb) of maximum torque in reverse.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Powerful reverse-bias 6-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 3-position power regulator in forward helps adjusting the power to the application.
- 360° swivel inlet helps eliminating twisted hoses.
- Silenced through-handle exhaust reduces the noise level.

Specifications at 6.2 bar (90 psi)

Part Number	2130XP
Ordering number	80136112
Drive size (square)	1/2 in
Other available versions:	
- forward torque limited	2130XP-TL
- kit with 10 short sockets	2130XP-K
- kit with 3 long sockets	2130XP+SK4M3L

PERFORMANCE

Working torque in forward	25 - 350 ft-lb / 34 - 474 Nm
Maximum torque in reverse	602 ft-lb / 816 Nm
Recommended fastener size	9/16 in / M14
Free speed	9 500 rpm
Impacts per minute	1 200

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4.4 CFM / 125 L/min
Air consumption at load	22.0 CFM / 623 L/min

NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	94.3 / 105.3 dB(A)
Free speed sound pressure / power (ISO15744)	90.8 / 101.8 dB(A)
Vibration level / measurement uncertainty (ISO28927)	8.9 / 2.0 m/s ²

WEIGHT & DIMENSIONS

Tool weight	4.20 lb / 1.90 kg
Tool dimensions (L x W x H)	187 x 72 x 182 mm
Shipping weight	5.10 lb / 2.30 kg
Shipping dimensions (L x W x H)	240 x 215 x 83 mm
UPC / EAN code	6 63023 01804 1
Origin	Made in China





SK4M3L
81287377
1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



SK4M14
81287351
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



Impact sockets
For the complete range, see our accessory catalogue.



2131-366
04706388
Horizontal hanger



2130-BOOT
45505369
Protective tool boot



33104
91486330
Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



115-LBK1
04616108
Lubricant kit for Impacttools™ with composite housing



115-4T
04616157
Grease for Impacttools with composite housing



SK4M5L
81287369
1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



SK4M18
81287385
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



4UA9
03070216
1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)



BMDS-4
92842087
Cable balancer, 2-4 kg, 2 m (6-1/2 ft)



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



Quick Release Couplings
For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



Lubricants
For the complete range, see our accessory catalogue.