



Perfect for any maintenance or repair application, the 2161XP delivers plenty of power and superior control, along with unmatched reliability that comes from more than a century of proven engineering and innovation.

- 1 695 Nm (1 250 ft-lb) of maximum torque.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- Steel hammercase provides superior durability under the toughest use.
- Powerful 6-vane motor delivers superior performance.
- Ergonomic handle design and textured finish provide a secure and comfortable grip.
- Feather-touch trigger allows precise delivery of power and speed.
- 3-position power regulator and forward/reverse control.
- Through-handle exhaust directs air away from the operator.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.

Specifications at 6,2 bar (90 psi)

Part Number	2161XP
Ordering number	01372085
Drive size (square)	3/4 in
Other available versions:	
- 3/4" square drive, 150 mm (6") extended anvil	2161XP-6
- 1" square drive, standard length anvil	2171XP
- 1" square drive, 150 mm (6") extended anvil	2171XP-6

PERFORMANCE

Working torque	300 - 1 000 ft-lb / 407 - 1356 Nm
Maximum torque	1 250 ft-lb / 1 695 Nm
Recommended fastener size	1 in / M25
Free speed	6 000 rpm
Impacts per minute	1 025

AIR SYSTEM

Air Inlet (NPTF)	3/8 in
Minimum hose size	1/2 in / 13 mm
Average air consumption	10 CFM / 280 L/min
Air consumption at load	46 CFM / 1 288 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)	94,7 / 105,7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	9,8 / 1,8 m/s ²

WEIGHT & DIMENSIONS

Tool weight	11,8 lb / 5,35 kg
Tool dimensions (L x W x H)	216 x 95 x 240 mm
Shipping weight	13,4 lb / 6,11 kg
Shipping dimensions (L x W x H)	310 x 295 x 115 mm
UPC / EAN code	6 63023 01061 8
Origin	Made in China





SK6M6L
81287401
3/4" Impact socket set (6 pcs) (24, 27, 30, 32, 33 and 36 mm)



E6175MM
81286130
3/4" Extension 175 mm



E6100MM
81286122
3/4" Extension 100 mm



Impact sockets
For the complete range, see our accessory catalogue.



2161-366
04621751
Horizontal hanger



BMDLN-8
17023755
Cable balancer, 6-8 kg, 2,5 m (8-1/4 ft)



2161-BOOT
45505401
Protective tool boot



2161-123
04621702
Piped-away exhaust hose adapter



33204-45
92938778
Hose whip, 3/8" NPT, 10 mm inside diameter, 45 cm (1,5 ft)



IB8NMC3
88103304
IBN/IBS Series nipple, 3/8" male thread, 8 mm bore (ISO6150B / MIL-C4109)



77NMC3
88104088
7N7/7S7 Series nipple, 3/8" male thread, 7,2 mm bore (EURO 7,2 - 7,4)



Quick Release Couplings
For the complete range, see our accessory catalogue.



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



105-LBK1
04616090
Lubricant kit for Impacttools™ with metal housing



10Z4
03875671
Oil, Class 1, no. 10, 0,12 L



105-4T-6
04618930
Grease for Impacttools hammer mechanism (6 tubes)



Lubricants
For the complete range, see our accessory catalogue.



2161-TK2
04621744
Motor service kit