



**This powerful and high quality drill is ideal for all general purpose drilling, honing, reaming and hole-sawing.**

- Powerful motor delivers 0,37 kW (0,50 HP).
- 2 000 rpm free speed.
- Planetary gear reduction balances the load on bearings and gears for increased tool life.
- Professional keyless chuck increases productivity by speeding bit changeovers and eliminating downtime by loss of drill key.
- Variable-speed trigger allows easy starts.
- Through-handle exhaust directs air away from the operator.



### Specifications at 6,2 bar (90 psi)

Part Number	<b>7802AKC</b>
Ordering number	<b>10563716</b>
Chuck capacity	<b>3/8 in / 10 mm</b>
Chuck type	<b>keyless</b>
Spindle size	<b>3/8"-24</b>
Available versions:	
- standard chuck, non-reversible	<b>7802A</b>
- standard chuck, reversible	<b>7802RA</b>
- keyless chuck, reversible	<b>7802RAKC</b>

### PERFORMANCE

Rated power	<b>0,50 HP / 0,37 kW</b>
Free speed	<b>2 000 rpm</b>

### AIR SYSTEM

Air Inlet (NPTF)	<b>1/4 in</b>
Minimum hose size	<b>10 mm</b>
Average air consumption	<b>4,0 CFM / 113 L/min</b>
Air consumption at load	<b>26,0 CFM / 736 L/min</b>

### NOISE & VIBRATION

Sound pressure / power (ISO15744)	<b>83,0 / 94,0 dB(A)</b>
Vibration level / measurement uncertainty (ISO28927)	<b>2,8 / 0,7 m/s<sup>2</sup></b>

### WEIGHT & DIMENSIONS

Tool weight	<b>2,97 lb / 1,35 kg</b>
Tool dimensions (L x W x H)	<b>175 x 46 x 156 mm</b>
Shipping weight	<b>3,45 lb / 1,57 kg</b>
Shipping dimensions (L x W x H)	<b>180 x 240 x 60 mm</b>
UPC / EAN code	<b>6 63023 01982 6</b>
Origin	<b>Made in China</b>

[www.ingersollrandproducts.com](http://www.ingersollrandproducts.com)

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



**728-99-KC5**  
04276564  
Keyless chuck, 10 mm



**7811-99**  
89930754  
Standard chuck, 10 mm



**7811-253**  
89930762  
Key for standard chuck, 10 mm



**7802-BOOT**  
45524279  
Protective tool boot



**IB6NMC2**  
88103015  
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



**77NMC2**  
88104070  
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7,2 - 7,4)



**Quick Release Couplings**  
For the complete range, see our accessory catalogue.



**Filters, regulators, lubricators**  
For the complete range, see our accessory catalogue.



**10Z4**  
03875671  
Oil, Class 1, no. 10, 0,12 L



**Lubricants**  
For the complete range, see our accessory catalogue.