

Ingersoll Rand **88V60P109M-EU** 230 mm (9") vertical grinder



Ingersoll Rand Pro-Series grinders and sanders are specially designed for heavy-duty production applications. With their superior power output, they are best suited for big tasks involving heavy material removal in foundries, welding shops, fabrication facilities, steel mills or shipyards.

- Powerful motor delivers 1.56 kW (2.1 HP).
- 6 000 rpm free speed.
- Auto-balancing system significantly reduces vibrations and increases the life of grinding discs, thus increasing user comfort and productivity.
- Internal governor maximizes speed under load, increasing your rate of material removal.
- Built-in mist lubricator automatically oils motor when throttle is activated.
- Integral trigger safety lock prevents accidental tool start.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.



Specifications at 6.2 bar (90 psi)

Part Number	88V60P109M-EU
Ordering number	01337716
Wheel type	Type 27
Wheel type	Type 28
Wheel capacity	9 in / 230 mm
Maximum wheel thickness	1/4 in / 6 mm
Spindle size	5/8"-11
Other available versions:	
- 180 mm (7") wheel capacity	88V85P107M-EU

PERFORMANCE

Rated power	2.1 HP / 1.56 kW
Free speed	6 000 rpm

AIR SYSTEM

Air Inlet (NPT)	1/2 in
Minimum hose size	3/4 in / 19 mm
Air consumption at load	61 CFM / 29.0 L/s

NOISE & VIBRATION

Sound pressure / power (ISO15744)	89.2 / 102.2 dB(A)
Vibration level / measurement uncertainty (ISO28927)	3.6 / 1.1 m/s ²

WEIGHT & DIMENSIONS

Tool weight	9.13 lb / 4.15 kg
Height over spindle	6.09 in / 155 mm
Shipping weight	11.7 lb / 5.3 kg
Shipping dimensions (L x W x H)	290 x 400 x 200 mm
UPC / EAN code	6 63024 00358 9
Origin	Made in the USA



www.ingersollrandproducts.com

Ingersoll Rand **88V60P109M-EU** ACCESSORIES



88V60-K184
03643962
Piped-away exhaust kit



33304
91488205
Hose whip, 1/2" NPT, 13 mm inside diameter, 30 cm (1 ft)



Quick Release Couplings
For the complete range, see our accessory catalogue.



CO-1518
56753122
Hose clamps, 15-18 mm outside diameter, 100 pcs



50P
03875705
Oil, Class 1, no. 50, 0.5 L



IB11NMC4
25014036
IBN/IBS Series nipple, 1/2" male thread, 11 mm bore (ISO6150B / MIL-C4109)



RH-12
92536051
PVC hose, 13 mm inside diameter, 30 m



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



88V 88H-TK3
03802915
Motor service kit

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

© 2008 Ingersoll-Rand Company — Form No. PDS_88V60P109M-EU_EN_2/2_12/09/2011

 **Ingersoll Rand**
Industrial Technologies