



Convenience of Cordless. Power of Air. The Ingersoll Rand W5130 20V Impactool delivers the power you need where you need it — from the engine compartment to the maintenance department. Designed for professional service technicians, the W5130 offers except

- 260 Nm (190 ft-lb) of maximum torque in reverse.
- All-metal impact mechanism and drive train provide the ultimate in durability and reliability.
- Engineered composite housing for increased protection against chemical attack.
- Steel-reinforced housings add strength for unmatched drop resistance.
- Over-molded soft-touch grip minimizes vibration, reduces fatigue and enhances user comfort.
- Variable speed switch with electronic brake provides maximum control of the tool.
- Convenient one-hand operation with reverse control at trigger.
- Compatible with high-capacity 3.0 Ah battery for maximum runtime or compact 1.5 Ah battery for reduced tool weight.
- Tool only is delivered without battery and charger. Kit contains: cordless tool, charger, 2 pcs 20 V, 1.5 Ah Li-ion batteries and blow molded case.

Specifications

Part Number	W5130
Ordering number (tool only)	48377840IR1
Part Number (kit)	W5130EU-K2
Ordering number (kit)	47497441001
Voltage (DC)	20 V
Drive size (square)	3/8 in
Other available versions:	
- 1/2" square drive	W5150

PERFORMANCE

Working torque with BL2005 battery	25 - 135 ft-lb / 35 - 180 Nm
Working torque with BL2010 battery	25 - 140 ft-lb / 35 - 190 Nm
Maximum torque in reverse with BL2005 battery	180 ft-lb / 245 Nm
Maximum torque in reverse with BL2010 battery	190 ft-lb / 260 Nm
Free speed	0 - 1 700 rpm
Impacts per minute	2 900

NOISE & VIBRATION

Sound pressure / power (EN60745)	91.0 / 102.0 dB(A)
Vibration level / measurement uncertainty with BL2005 battery (EN60745)	8.8 / 2.6 m/s ²
Vibration level / measurement uncertainty with BL2010 battery (EN60745)	9.8 / 1.8 m/s ²

WEIGHT & DIMENSIONS

Tool weight without battery	2.65 lb / 1.20 kg
Tool weight with BL2005 battery	3.60 lb / 1.60 kg
Tool weight with BL2010 battery	4.10 lb / 1.90 kg
Tool length	6.6 in / 168 mm
Shipping weight (tool only)	3.50 lb / 1.59 kg
Shipping weight (kit)	11.30 lb / 5.10 kg
Shipping dimensions (tool only) (L x W x H)	216 x 216 x 89 mm
Shipping dimensions (kit) (L x W x H)	470 x 390 x 130 mm
UPC / EAN code (tool only)	6 63024 005934
UPC / EAN code (kit)	6 63024 006382
Origin	Made in China





SK3M10
81287344
3/8" Impact socket set (10 pcs) (9, 10, 11, 12, 13, 14, 15, 16, 17 and 19 mm)



Impact sockets
For the complete range, see our accessory catalogue.



W5000-CASE
48622104
Carrying case



W5130-BOOT
48624753
Protective tool boot



BL2005
48386783
Li-Ion battery, 20 V, 1.5 Ah



BL2010
48386791
Li-Ion battery, 20 V, 3.0 Ah



BC1120-EU
17028960
Universal battery charger



L5110
48489561
Task light (without battery)



67-4T
04637336
Grease for high-speed angle heads



105-4T-6
04618930
Grease for Impacttools hammer mechanism (6 tubes)