

New



From Ingersoll Rand, the company that invented the Impactool in 1934, comes a revolutionary product that is unlike any other on the market today. The Hammerhead low profile right-angle Impactool offers the power of an impact with the reach of a ratchet and it's going to change the way you work and boost productivity.

- 244 Nm (180 ft-lb) of maximum torque in reverse delivered by a tool that has the size and the reach of a ratchet wrench.
- A head height of under 50 mm allows the tool to be used in tight spaces.
- The impact mechanism ensures no torque reaction.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability.
- Powerful reverse-bias 6-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 2-position power regulator in forward helps adjusting the power to the application.
- Conveniently located forward/reverse ring provides unrestricted access to easily change the direction of the tool.
- Rear exhaust directs air away from the operator.

Specifications at 6,2 bar (90 psi)

Part Number	2025MAX
Ordering number	47099247
Drive size (square)	1/2 in
Available versions:	
- 3/8" square drive	2015MAX

PERFORMANCE

Working torque in forward	45 - 140 ft-lb / 61 - 190 Nm
Maximum torque in forward	150 ft-lb / 203 Nm
Working torque in reverse	45 - 160 ft-lb / 61 - 217 Nm
Maximum torque in reverse	180 ft-lb / 244 Nm
Recommended fastener size	7/16 in / M11
Free speed	7 100 rpm
Impacts per minute	2 100

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	3,5 CFM / 99 L/min
Air consumption at load	19,0 CFM / 538 L/min

NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	96,6 / 107,6 dB(A)
Free speed sound pressure / power (ISO15744)	94,1 / 105,1 dB(A)
Vibration level / measurement uncertainty (ISO28927)	17,4 / 3,0 m/s ²

WEIGHT & DIMENSIONS

Tool weight	3.4 lb / 1,54 kg
Tool length	13.1 in / 332 mm
Head dimensions (W x H)	2.2 x 2.0 in / 56 x 50 mm
Shipping weight	4.2 lb / 1,90 kg
Shipping dimensions (L x W x H)	165 x 368 x 64 mm
UPC / EAN code	6 63023 08866 2
Origin	Assembled in the USA

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



SK4M14
81287351
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)

Impact sockets

For the complete range, see our accessory catalogue.



SK4M18
81287385
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)

IB6NMC2

88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2

88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7,2 - 7,4)



Couplings

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



115-LBK1

04616108
Lubricant kit for Impacttools™ with composite housing



10Z4

03875671
Oil, Class 1, no. 10, 0,12 L



115-4T-6

04618948
Grease for Impacttools with composite housing (6 tubes)



Lubricants

For the complete range, see our accessory catalogue.



2015-THK

47100359
Impact mechanism service kit



2015-TK

47100474
Motor service kit

