



Compensated HP Hand Pumps



Fisher Offshore has a range of single and double acting hand pumps for deck use and compensated for use subsea.

Compensated HP Hand Pumps	EQ1000	NK2236
Pump Type	2 stage (2 speed)	2 stage (2 speed)
Double Acting	Yes	Yes
Max Working Pressure (Stage 1)	13.8 Bar (197Psi)	30 Bar (435Psi)
Max Working Pressure (Stage 2)	700 Bar (10000Psi)	700 Bar (10000Psi)
Compensated for Subsea use	Yes	Yes
Subsea Pressure Gauge	Yes	Yes
Oil Reservoir Capacity	1000cc	500cc
Stroke Volume (stage 1)	3.62cc	20cc
Stroke Volume (stage 2)	0.77cc	1cc
Connection Type	3/8" Pioneer Quick Coupling	3/8" Pioneer Quick Coupling
Handle Effort to Achieve Max WP	21kgF	38kgF
Dimensions (L x W x H)	770mm x 182mm x 206mm	700mm x 140mm x 230mm
Foot Plate Dimensions (optional)	n/a	610mm x 400mm x 6mm
Weight	8.0kg	17kg (inc Foot Plate)
Options	HP Hose (length to be specified) c/w 3/8" Pioneer Quick Couplings. Oil reservoir capacity can be increased with the addition of an external bladder for applications where internal reservoir is insufficient.	



For more information on how Fisher Offshore can add value to your offshore operations visit www.fisheroffshore.com or contact one of our specialist consultants at info@fisheroffshore.com or call +44 (0) 1651 87 39 32

Fisher Offshore, North Meadows, Oldmeldrum, Aberdeenshire, Scotland AB51 0GQ