

**New**



**Perfect for any maintenance or repair application, the 2125PTiMAX delivers maximum power and control, along with unmatched reliability that comes from more than a century of proven engineering and innovation.**

- 450 Nm (332 ft-lb) of maximum torque in reverse - that's the best-in-class performance.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Titanium hammercase is lightweight with unparalleled durability.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.
- FREE two-year limited warranty with tool registration.

### Specifications at 6,2 bar (90 psi)

Part Number	2125PTiMAX
Ordering number	45587565
Drive size (square)	1/2 in
Socket retainer type	pin-type
Other available versions: - 3/8" square drive	2115PTiMAX

### PERFORMANCE

Working torque in forward	25 - 251 ft-lb / 34 - 340 Nm
Maximum torque in forward	277 ft-lb / 375 Nm
Working torque in reverse	302 ft-lb / 410 Nm
Maximum torque in reverse	332 ft-lb / 450 Nm
Recommended fastener size	7/16 in / M11
Free speed	15 000 rpm
Impacts per minute	1 500

### AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Air consumption at load	17,0 CFM / 8,0 L/s

### NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	93,2 / 104,2 dB(A)
Free speed sound pressure / power (ISO15744)	89,7 / 100,7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	7,5 / 1,8 m/s <sup>2</sup>

### WEIGHT & DIMENSIONS

Tool weight	2.51 lb / 1,14 kg
Tool dimensions (L x W x H)	151 x 56 x 171 mm
Shipping weight	3.31 lb / 1,50 kg
Shipping dimensions (L x W x H)	238 x 213 x 79 mm
UPC / EAN code	6 63023 04316 6
Origin	Assembled in the USA



[www.ingersollrandproducts.com](http://www.ingersollrandproducts.com)

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.


**SK4M14**

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)

**Impact sockets**

For the complete range, see our accessory catalogue.


**2112-366**

10323350

Horizontal hanger


**2115-BOOT**

45505351

Protective tool boot


**33104-45**

92938760

Hose whip, 1/4" NPT, 6 mm inside diameter, 45 cm (1,5 ft)


**77NMC2**

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7,2 mm bore (EURO 7,2 - 7,4)


**Filters, regulators, lubricators**

For the complete range, see our accessory catalogue.


**115-LBK1**

04616108

Lubricant kit for Impacttools™ with composite housing


**115-4T-6**

04618948

Grease for Impacttools with composite housing (6 tubes)


**2115-THK2**

45585932

Impact mechanism service kit


**SK4M18**

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)

**4UA9**

03070216

1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)


**BMSD-2**

92842152

Cable balancer, 1-2,5 kg, 2 m (6-1/2 ft)


**2115-K284**

45612637

Piped-away exhaust kit


**IB6NMC2**

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)


**Quick Release Couplings**

For the complete range, see our accessory catalogue.


**10Z4**

03875671

Oil, Class 1, no. 10, 0,12 L


**Lubricants**

For the complete range, see our accessory catalogue.


**2115-TK2**

45585189

Motor service kit

